

## PC/SC Contact Less READER ATT-5930



- ATT-5930 reader is a brand new reader developed by Emperor. It adopts ARM processor provides the fastest speed and reliable performance which also supports all contactless reading standards: ISO 14443 Type A, Type B, Type C, ISO18092 tags.
- ATT-5930 could run driver under systems includes but not limited to Wind98, Win NT, Win7. Offered DLL API interface allows the user develop their own system at fastest.

<b>Technical Parameters</b>	
	<b>Host Interface</b>
<b>Host Interface</b>	USB 2.0 CCID (also compliant with USB1 RS-485)
	<b>Supported Tags</b>
<b>ISO14443-Type A</b>	Mifare One S50; Mifare One S70; Mifare Ultra Light; Mifare Ultra Light C; Mifare DesFire; Mifare Plus (Full Functions) ISO14443-4 (T=CL) TYPE A Contact Less IC card
<b>ISO14443-Type B</b>	AT88RF020; AT88RF080; SRI176; SRI512; SRI1K; RI2K; SRI4K; SRIX4K; ISO14443-4 (T=CL) TYPE B Contact Less IC card
<b>ISO18092</b>	Felica
	<b>Antenna</b>
<b>Antenna</b>	Integrated
	<b>Driver</b>
<b>Operation System Supported</b>	No driver needed Win98, Win NT, Win7
	<b>Status Indicator</b>
<b>Two LED</b>	Green=ready, red=busy
	<b>Expansion Capacity</b>
<b>LCD Screen</b>	Avaliable to intergrate 2.0 6 LCD-1602 Screen
	<b>Power Supply</b>
<b>Power Supply</b>	USB
<b>Consumption</b>	Maximum: 150mA Buzzer
<b>Buzzer</b>	Integrated
	<b>Reading distance</b>
<b>Maximum Distance</b>	80 mm
	<b>Dimension</b>
<b>Dimension</b>	112(L) 82(W) 26(H)(mm)
	<b>Weight</b>
<b>Weight</b>	100 g
	<b>Operation temperature</b>
<b>Operating Temperature</b>	0-55 °C